

## Flexi 5W 3000K





## Product Code:

## EX0205-3000K

Electrical Data	
Voltage (V)	DC 24V
Frequency (Hz)	N/A
Constant Current (mA)	208
Power Factor	>0.4
Starting Time (sec)	<0.5
Warm-up Time Up to 100% of the Full Light Output (sec)	Instant full light
Product Data	
Lamp Base	N/A
Product Wattage (W)	5
Colour Temperature (K)	Warmwhite (3000K)
Colour Render Index (Ra)	Ra80
Colour Consistency (SDCM)	<6
Dimmable	Yes
Energy Label	A++
Operating Temperature	-30 ° C to +40 ° C
Switching Cycles (times)	>1000000
Mercury Content (mg)	N/A
Weight (g)	42
Application	Retail, Hospitality, Residential
Performance Data	
Total Luminous Flux (lm)	300
Rated Life (hrs)	25000
Lumen Maintenance at the End of Lamp Life (%)	90
IP Rating	IP68
Product Dimensions	
Length (mm)	1000
Width (mm)	14
Height (mm)	5
Remarks: The lamp is not suitable for accent lighting. Water resistant	



outdoor version, the lamp is designed to maintain the IP rating of the light fitting used (up to maximum of IP68). Capable of dimming when working with a pulse width modulation (PWM) dimmer. Dimming performance depends on the specification and quality of PWM dimmer.

The rated wattage, rated lamp life and rated luminous flux are equivalent to their nominal values shown on product packaging.