



# TOTT M Floodlight (Integrated) - IP65



Product Code:

**FFL70200v0**


Electrical Data	
Voltage (V)	220-240V
Power Factor	>0.9
Product Data	
Product Wattage (W)	24
Beam Angle ( ° )	100
Tilting Angle ( ° )	160
Colour Temperature (K)	Warmwhite (3000K), Coolwhite (4000K)
Colour Render Index (Ra)	>Ra80
Colour	Black (BK23)
Protection Class	Class II
Dimmable	No
Operating Temperature	-30 ° C to +40 ° C
Weight (g)	485
Application	Billboards, Gate areas, Pillar Facades, Signages
Performance Data	
Max. Luminous Intensity (cd)	1065
Luminous Flux (lm)	2300
Luminous Efficacy (lm/W)	96
Rated Life (hrs)	50000
IP Rating	IP65
Product Dimensions	
Length (mm)	179
Width (mm)	179
Height (mm)	138

Product Code: FFL70200v0

MEGAMAN® 2005-2018. All Rights Reserved.  
This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

[www.megaman.cc](http://www.megaman.cc)



m	Lux	Ø cm
0.5	4260	119
1	1065	238
1.5	473	358
2	266	477

Beam angle = 100°