


DINO 2 Waterproof Batten (Integrated) - Opal Prismatic Diffuser Options



Silver

| | | |
|------|------|----------|
| IP66 | IK08 | Class II |
|------|------|----------|



Product Code:

F61600SMv1


| Electrical Data | |
|--------------------------|---|
| Voltage (V) | 220-240V |
| Power Factor | >0.9 |
| Product Data | |
| Product Wattage (W) | 63 |
| Beam Angle (°) | 120 |
| Colour Temperature (K) | Warmwhite (3000K), Coolwhite (4000K) |
| Colour Render Index (Ra) | Ra80 |
| Colour | Silver (SV16) |
| Protection Class | Class II |
| Dimmable | No |
| Application | Car parks, Underground Areas, Warehouses, Workshops |
| Performance Data | |
| Luminous Flux (lm) | 6300 [3000K], 6500 [4000K] |
| Luminous Efficacy (lm/W) | 100 [3000K], 103 [4000K] |
| Rated Life (hrs) | 50000 hrs at L80, B10 at Ta 25 ° C |
| IP Rating | IP66 |
| Product Dimensions | |
| Length (mm) | 1572 |
| Width (mm) | 62 |
| Height (mm) | 56 |

Product Code: F61600SMv1

MEGAMAN® 2005-2018. All Rights Reserved.
This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

www.megaman.cc



| m | Lux | Ø cm |
|-----|------|------|
| 0.5 | 6800 | 173 |
| 1 | 1700 | 346 |
| 1.5 | 756 | 520 |
| 2 | 425 | 693 |

Beam angle = 120°