


DINO 2 Waterproof Batten (Integrated) - Opal Prismatic Diffuser Options - Permanent Live




Silver

IP66	IK08	Class II
------	------	----------



Integrated LED Luminaire
FOB61600v0-pl



Product Code:

FOB61600v0-pl

Electrical Data	
Voltage (V)	220-240V
Power Factor	>0.9
Product Data	
Product Wattage (W)	35
Beam Angle (°)	120
Colour Temperature (K)	Warmwhite (3000K), Coolwhite (4000K)
Colour Render Index (Ra)	Ra80
Colour	Silver (SV16)
Materials	Polycarbonate with opal prismatic diffuser
Protection Class	Class II
Dimmable	No
Application	Car parks, Underground Areas, Warehouses, Workshops
Performance Data	
Luminous Flux (lm)	3500 [3000K], 3600 [4000K]
Luminous Efficacy (lm/W)	100 [3000K], 103 [4000K]
Rated Life (hrs)	50000 hrs at L80, B10 at Ta 25 ° C
IP Rating	IP66
Product Dimensions	
Length (mm)	1572
Width (mm)	62
Height (mm)	56

Product Code: FOB61600v0-pl

MEGAMAN® 2005-2018. All Rights Reserved.
This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

www.megaman.cc

m	Lux	Ø cm
0.5	3920	173
1	980	346
1.5	436	520
2	245	693

Beam angle = 120°