



MARCO Mini Track Lighting (Integrated)





Class \parallel




Product Code:

FTA70000v0

Electrical Data		
	000 0401/	
Voltage (V)	220-240V	
Power Factor	>0.9	
Product Data		
Product Wattage (W)	12	
Beam Angle (°)	12, 24, 36	
Rotating Angle (°)	330	
Tilting Angle (°)	90	
Colour Temperature (K)	Warmwhite (2800K), Coolwhite (4000K)	
Colour Render Index (Ra)	Ra80	
Colour Consistency (SDCM)	6	
Colour	White (WH26), Silver (SV28), Black (BK24)	
Materials	Aluminium	
Protection Class	Class	
Dimmable	No	
Operating Temperature	-30 ° C to +40 ° C	
Application	Hotels, Museums, Restaurants, Shop Lighting, Showrooms	
Performance Data		
Max. Luminous Intensity (cd)	10000 [12 °], 5500 [24 °], 2650 [36 °]	
Luminous Flux (lm)	900 [2800K/12°], 950 [4000K/12°], 950 [2800K/24°/36°], 1000 [4000K/24°/36°]	
Luminous Efficacy (lm/W)	75 [2800K/12 °], 79 [4000K/12 °], 79 [2800K/24 ° /36 °], 83 [4000K/24 ° /36 °]	
Rated Life (hrs)	25000hrs at L70 B50 at Ta 25 ° C	
Product Dimensions		
Diameter (mm)	50	
Height (mm)	128	

Product Code: FTA70000v0







m	Lux	Ø cm
0.5	22000	21
_1	5500	43
1.5	2444	64
2	1375	85

Beam angle = 24°

FTA70000v0-36 °





Remarks: Accessories:

LA10034 Honeycomb louver

