


PINOLITE Batten (Integrated)




White

IK03	IP20	Class II
------	------	----------



Integrated LED Luminaire
FIB71500v0-3000K



Product Code:

FIB71500v0

Electrical Data

Voltage (V)	220-240V
-------------	----------

Product Data

Product Wattage (W)	12
Colour Temperature (K)	Warmwhite (3000K), Coolwhite (4000K), Daylight (6500K)
Colour Render Index (Ra)	>Ra80
Colour	White (WH13)
Materials	Polycarbonate
Protection Class	Class II
Dimmable	No
Operating Temperature	-30 ° C to +40 ° C
Application	Office, Display Shelves, Light Troughs, Shops and Boutiques, Wall Lighting

Performance Data

Luminous Flux (lm)	1000 [3000K], 1100 [4000K/6500K]
Luminous Efficacy (lm/W)	83 [3000K], 92 [4000K/6500K]
Rated Life (hrs)	35000 hrs at L70 B50 at Ta 25 ° C
IP Rating	IP20

Product Dimensions

Length (mm)	580
Width (mm)	23
Height (mm)	39

Remarks: Accessories:
 LA8002 1.8m Power Cord
 LA8036 150mm Patch Cord
 LA8004 Angle Joint for PINOLITE
 LA8005 Mounting Clips (Comes with the MEGAMAN® PINO)
 LA8039 Female Pole Protective Cap

Product Code: FIB71500v0

MEGAMAN® 2005-2018. All Rights Reserved.
 This document is for informational purpose only.


MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

www.megaman.cc

m	Lux	Ø cm
0.5	1040	173
1	260	346
1.5	116	520
2	65	693

Beam angle = 120°


FIB71500v0-4000K



m	Lux	Ø cm
0.5	1120	173
1	280	346
1.5	124	520
2	70	693

Beam angle = 120°

FIB71500v0-6500K



Product Code: FIB71500v0

MEGAMAN® 2005-2018. All Rights Reserved.
This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

www.megaman.cc

