



## CARLO Adjustable Recessed Downlight (RDx) DIMMABLE








Product Code:

## F28249RC-p

Electrical Data			
Nominal Voltage (V)	DC 40- 46V		
Input Current (mA)	700		
Product Data			
Product Wattage (W)	31		
Light Source	TECOH® RDx RD0555M-p with input current 700mA		
Beam Angle (°)	35, 60		
Rotating Angle (°)	355		
Tilting Angle (°)	45		
Colour Temperature (K)	Warmwhite (3000K)		
Colour Render Index (Ra)	Ra82		
Colour	White (WH26), Silver (SV26)		
Materials	Metal housing		
Protection Class	Class III		
Dimmable	Yes		
Suggested Driver	LA11053		
Weight (g)	1065		
Application	Commercial buildings, Department Stores, Exhibition Booths, Galleries and Museums, Shops and Boutiques		
Performance Data			
Max. Luminous Intensity (cd)	5500 [35 ° ], 3500 [60 ° ]		
Luminous Flux (lm)	2400 [3000K]		
Luminous Efficacy (Im/W)	77 [3000K]		
Rated Life (hrs)	50000		
IP Rating	IP20		
Product Dimensions			
Diameter (mm)	170		
Height (mm)	135		
Cut-out (mm)	Ø155		
Remarks: Capable of linear dimming when working with DALI, DSI or			

Product Code: F28249RC-p






m	Lux	Ø cm
0.5	22000	32
1	5500	63
1.5	2444	95
2	1375	126

Beam angle = 35°

## F28249RC-p-60°



m	Lux	Ø cm	
0.5	14000	58	
1	3500	115	
1.5	1556	173	
2	875	231	
Beam angle = 60°			

1-10V dimming driver, and the dimming performance depends on the specification of driver. The wattage declared is the wattage of the luminaire without driver; the system wattage will be dependent on driver choice. Different reflectors options available: LA3107 35  $^{\circ}$  Reflector, LA3107 60  $^{\circ}$  Reflector

## Technologies



Offering retailers a distinct advantage to enhance textiles by bringing whites to life while still offering superb efficacy and energy efficiency, compared to traditional light sources.