




## SIENA Recessed Downlight (Integrated)







## Integrated LED Luminaire F26300RC



Product Code:

## F26300RC

| Electrical Data               |                                                        |  |
|-------------------------------|--------------------------------------------------------|--|
| Voltage (V)                   | 220-240V                                               |  |
| Power Factor                  | >0.9                                                   |  |
| Product Data                  |                                                        |  |
| Product Wattage (W)           | 20.5                                                   |  |
| Colour Temperature (K)        | Warmwhite (2800K), Coolwhite (4000K), Daylight (6500K) |  |
| Colour Render Index (Ra)      | >Ra80                                                  |  |
| Colour                        | White (WH26), Silver (SV26)                            |  |
| Materials                     | Metal housing with plastic diffuser                    |  |
| Protection Class              | Class I                                                |  |
| Dimmable                      | No                                                     |  |
| Weight (g)                    | 266                                                    |  |
| Performance Data              |                                                        |  |
| Luminous Flux (lm)            | 1560                                                   |  |
| Luminous Efficacy (lm/W)      | 76                                                     |  |
| Rated Life (hrs)              | 25000                                                  |  |
| IP Rating                     | IP44                                                   |  |
| Product Dimensions            |                                                        |  |
| Diameter (mm)                 | 172                                                    |  |
| Height (mm)                   | 94                                                     |  |
| Cut-out (mm)                  | Ø150                                                   |  |
| Remarks: Surface Mount Kit: L | A10017                                                 |  |

Product Code: F26300RC



| m         | Lux     | Ø cm |
|-----------|---------|------|
| 0.5       | 3240    | 100  |
| _1_/      | 810     | 200  |
| 1.5       | 360     | 300  |
| 2         | 203     | 400  |
| Beam angl | e = 90° |      |