


# SIENA Adjustable Recessed Downlight (Integrated) - High Output



**High Output**



Integrated LED Luminaire  
F28100RCv1-24 °

Product Code:

**F28100RCv1**


Electrical Data	
Voltage (V)	220-240V
Product Data	
Product Wattage (W)	7.5
Beam Angle ( ° )	24, 36
Tilting Angle ( ° )	25
Colour Temperature (K)	Warmwhite (2800K), Coolwhite (4000K)
Colour Render Index (Ra)	>Ra80
Colour	White (WH26), Silver (SV26), Brushed Nickel (NI53)
Materials	Metal housing with diffuser
Protection Class	Class II
Dimmable	No
Weight (g)	180
Performance Data	
Max. Luminous Intensity (cd)	3650 [24 ° ], 2000 [36 ° ]
Luminous Flux (lm)	650
Luminous Efficacy (lm/W)	87
Rated Life (hrs)	25000
IP Rating	IP44
Product Dimensions	
Diameter (mm)	80
Height (mm)	55
Cut-out (mm)	Ø68

Product Code: F28100RCv1

MEGAMAN® 2005-2018. All Rights Reserved.  
This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.


[www.megaman.cc](http://www.megaman.cc)



m	Lux	Ø cm
0.5	14600	21
1	3650	43
1.5	1622	64
2	913	85

Beam angle = 24°

F28100RCv1-36 °



m	Lux	Ø cm
0.5	8000	32
1	2000	65
1.5	889	97
2	500	130

Beam angle = 36°

Product Code: F28100RCv1

MEGAMAN® 2005-2018. All Rights Reserved.  
This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

[www.megaman.cc](http://www.megaman.cc)