


SIENA SR Recessed Downlight (Integrated) DIMMABLE










Integrated LED Luminaire F54200RC-d



Product Code: F54200RC-d

Product Code:

F54200RC-d

Electrical Data	
Voltage (V)	220-240V
Power Factor	>0.9
Product Data	
Product Wattage (W)	16.5
Colour Temperature (K)	Warmwhite (2800K), Coolwhite (4000K), Daylight (6500K)
Colour Render Index (Ra)	>Ra80
Colour	White (WH26), Silver (SV26)
Materials	Die-cast aluminium trim with specular reflector
Protection Class	Class II
Dimmable	100-5%
Performance Data	
Luminous Flux (lm)	1560
Luminous Efficacy (lm/W)	95
Rated Life (hrs)	50000
IP Rating	IP44
Product Dimensions	
Diameter (mm)	172
Height (mm)	94
Cut-out (mm)	Ø150
Remarks: UGR 22	

Remarks: UGR 22 Shielding Angle: Up to 25 °

Capable of linear dimming from 100% to 5% when working with most

conventional dimmers.

Technologies



Compatible with the widest range of existing dimmers, whether they are leading-edge or trailing edge dimmers, with enhanced dimming range of 100% to 5%.



m	Lux	Ø cm
0.5	3400	100
1	850	200
1.5	378	300
2	213	400
Beam and	gle = 90°	