


U-DIM-SIENA FR Recessed Downlight (Integrated) DIMMABLE



White




Silver




IP44

Class II



Integrated LED Luminaire
F54700RC-d



Product Code:

F54700RC-d

Electrical Data

Voltage (V)	220-240V
Power Factor	>0.9

Product Data

Product Wattage (W)	16.5
Colour Temperature (K)	Warmwhite (2800K), Coolwhite (4000K), Daylight (6500K)
Colour Render Index (Ra)	>Ra80
Colour	White (WH26), Silver (SV26)
Materials	Die-cast aluminium trim with specular reflector
Protection Class	Class II
Dimmable	100-5%

Performance Data

Luminous Flux (lm)	1560
Luminous Efficacy (lm/W)	95
Rated Life (hrs)	50000
IP Rating	IP44

Product Dimensions

Diameter (mm)	172
Height (mm)	94
Cut-out (mm)	Ø150

Remarks: UGR 22

Shielding Angle: Up to 25 °

Capable of linear dimming from 100% to 5% when working with most conventional dimmers

Technologies




Compatible with the widest range of existing dimmers, whether they are leading-edge or trailing edge dimmers, with enhanced dimming range of 100% to 5%.

Product Code: F54700RC-d

MEGAMAN® 2005-2018. All Rights Reserved.
This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

www.megaman.cc



m	Lux	Ø cm
0.5	3400	100
1	850	200
1.5	378	300
2	213	400

Beam angle = 90°