



SIENA FR Recessed Downlight (Integrated)







Integrated LED Luminaire F54700RC



Product Code:

F54700RC

| Electrical Data | | |
|--|---|--|
| Voltage (V) | 220-240V | |
| Power Factor | >0.9 | |
| Product Data | | |
| Product Wattage (W) | 15.5 | |
| Colour Temperature (K) | Warmwhite (2800K), Coolwhite (4000K), Daylight (6500K) | |
| Colour Render Index (Ra) | >Ra80 | |
| Colour | White (WH26), Silver (SV26) | |
| Materials | Die-cast aluminium trim with specular reflector | |
| Protection Class | Class II | |
| Dimmable | No | |
| Performance Data | | |
| Luminous Flux (Im) | 1560 | |
| Luminous Efficacy (Im/W) | 101 | |
| Rated Life (hrs) | 50000 | |
| IP Rating | IP44 | |
| Product Dimensions | | |
| Diameter (mm) | 172 | |
| Height (mm) | 94 | |
| Cut-out (mm) | Ø150 | |
| Remarks: UGR 22 Shielding Angle: Up to 25 ° | | |

Product Code: F54700RC

MEGAMAN[®] 2005-2018. All Rights Reserved.

This document is for informational purpose only. MEGAMAN[®] reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein. www.megaman.cc Page 1 of 2



| m | Lux | Øcm |
|-----|------|-----|
| 0.5 | 3400 | 100 |
| 1 | 850 | 200 |
| 1.5 | 378 | 300 |
| 2 | 213 | 400 |

Beam angle = 90°

Product Code: F54700RC