

DINO 2 Waterproof Batten (Integrated) - Opal Prismatic Diffuser Options




Silver


IP66

IK08

Class
II



Integrated LED Luminaire
F61600SM



Product Code:

F61600SM

Electrical Data

Voltage (V)	220-240V
Power Factor	>0.9

Product Data

Product Wattage (W)	35
Beam Angle (°)	120
Colour Temperature (K)	Warmwhite (3000K), Coolwhite (4000K)
Colour Render Index (Ra)	Ra80
Colour	Silver (SV16)
Materials	Polycarbonate with opal prismatic diffuser
Protection Class	Class II
Dimmable	No
Application	Car parks, Underground Areas, Warehouses, Workshops

Performance Data

Luminous Flux (lm)	3500 [3000K], 3600 [4000K]
Luminous Efficacy (lm/W)	100 [3000K], 103 [4000K]
Rated Life (hrs)	50000 hrs at L80, B10 at Ta 25 ° C
IP Rating	IP66

Product Dimensions

Length (mm)	1572
Width (mm)	62
Height (mm)	56

Product Code: F61600SM

MEGAMAN® 2005-2018. All Rights Reserved.
This document is for informational purpose only.

MEGAMAN® reserves the right to make changes from time to time in the interest of product developments without prior notification to any products herein.

www.megaman.cc

m	Lux	Ø cm
0.5	3920	173
1	980	346
1.5	436	520
2	245	693

Beam angle = 120°