

GX53 6W GX53 2800K DIMMABLE





Product Code:

LR2206d-GX53-2800K-230V

Electrical Data	
Voltage (V)	220-240V
Power Factor	>0.5
Starting Time (sec)	<0.5
Warm-up Time Up to 100% of	Instant full light
the Full Light Output (sec)	
Product Data	
Lamp Base	GX53
Product Wattage (W)	6
Equivalent Wattage (W)	40
Reflector	GX53
Colour Temperature (K)	Warmwhite (2800K)
Colour Render Index (Ra)	Ra80
Colour Consistency (SDCM)	6
Dimmable	100-10%
Operating Temperature	-30 ° C to +40 ° C
Switching Cycles (times)	>1,000,000
Mercury Content (mg)	N/A
Weight (g)	68
Application	Hospitality
Performance Data	
Total Luminous Flux (lm)	40
Rated Life (hrs)	25000
Lumen Maintenance at the	90
End of Lamp Life (%)	
Product Dimensions	
Diameter (mm)	75
Length (mm)	24
Width (mm)	N/A
Height (mm)	N/A
Remarks: The rated lamp life, rated luminous flux in 90 ° cone, total	

Remarks: The rated lamp life, rated luminous flux in 90 ° cone, total luminous flux, rated beam angle and rated wattage are equivalent to their nominal values shown on product packaging. There is no



measurable output from 180nm to 380nm, so the chart shows only 380nm to 800nm.

Technologies



Being able to adjust your LEDs with wide selection of dimming range from 100% to 10% or 20% for perfect atmosphere and/or scene setting - warm and bright, dim and cozy.