



MARCO Track Lighting (Integrated) - Ultra RichColour





 \parallel



Product Code:

FTK70100v0-ru

| Voltage (V) | 220-240V |
|------------------------------|--|
| Power Factor | >0.9 |
| Product Data | |
| Product Wattage (W) | 37 |
| Beam Angle (°) | 12, 25, 45 |
| Rotating Angle (°) | 330 |
| Tilting Angle (°) | 90 |
| Colour Temperature (K) | Warmwhite (3000K), Coolwhite (4000K) |
| Colour Render Index (Ra) | Ra97 |
| Colour Consistency (SDCM) | 3 |
| Colour | White (WH26), Silver (SV28), Black (BK24) |
| Materials | Aluminium |
| Protection Class | Class |
| Dimmable | No |
| Operating Temperature | -30 ° C to +40 ° C |
| Application | Bus and Train Terminus, Hotels, Museums, Restaurants, Shop Lighting, Showrooms |
| Performance Data | |
| Max. Luminous Intensity (cd) | 14000 [25 °], 5400 [45 °] |
| Luminous Flux (Im) | 2400 [3000K], 2500 [4000K] |
| Luminous Efficacy (Im/W) | 65 [3000K], 68 [4000K] |
| Rated Life (hrs) | 50000hrs at L70 B50 at Ta 25 ° (|
| Product Dimensions | |
| Diameter (mm) | 110 |
| Height (mm) | 248 |
| Remarks: Accessories: | |
| LA10054 Spread lens | LA10055 Rectangular lens |

Product Code: FTK70100v0-ru



